



04000 Motor Oil 10W-40 Semi Synthetic

Document version: May 18, 2024



Description

This semi synthetic universal motor oil has been developed for normal duty petrol, LPG and diesel engines of cars and light commercial vehicles.

According to the specifications of

ACEA A3/B4
API CF / SN
Fiat 9.55535-D2 / 9.55535-G2
MB 229.1
VW 501.01 / 502.00 / 505.00

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 04001 | 1 L | 6 | 450 |
| 04004 | 4 L | 4 | 112 |
| 04005 | 5 L | 4 | 112 |
| 04020 | 20 L | 1 | - |
| 04060 | 60 L | 1 | - |
| 04205 | 205 L | 1 | 2 |
| 04999 | 1000 L | 1 | - |
| P04000 | 1 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|------------------------------|--------|--------------------|---------------|
| Density at 15°C | 0,858 | kg/l | ASTM D4052 |
| Viscosity | 10W-40 | | SAE |
| Kinematic Viscosity at 40°C | 91 | mm ² /s | ASTM D445 |
| Kinematic Viscosity at 100°C | 14.1 | mm ² /s | ASTM D445 |
| Viscosity Index | 159 | | ASTM D2270 |
| Flashpoint COC | 225 | °C | ASTM D92 |
| Pourpoint | -39 | °C | ASTM D6892 |
| Total Base Number | 10.2 | mgKOH/g | ASTM D2896 |

These characteristics are typical of current production. Variations in these characteristics may occur.