



10000LS Gear Oil SAE 90 GL-5 Mineral Limited Slip

Document version: 18 May 2024



Description

This mineral SAE 90 Limited Slip gear oil has been specially developed for heavy duty hypoid drives in rear axles and all transmissions where a Limited Slip SAE 80W-90 GL-5 or Limited Slip SAE 90 GL-5 is recommended.

According to the specifications of

API GL-5 Limited Slip
Ford M2C104-A
ZF TE-ML 05C / 12C / 16E

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
10001LS	1 L	6	450
10020LS	20 L	1	30
10060LS	60 L	1	6
10205LS	205 L	1	2
10999LS	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density	0.900	kg/l	ASTM D4052
Viscosity	SAE 90		SAE
Kinematic Viscosity at 40°C	145	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	14.4	mm ² /s	ASTM D445
Viscosity Index	97		ASTM D2270
Flashpoint	210	°C	ASTM D92
Pourpoint	-30	°C	ASTM D6892
Brookfield Viscosity at -26°C	130000	mPa.s	ASTM D2983

These characteristics are typical of current production. Variations in these characteristics may occur.