



36000 STOU 15W-30 GL-4 Multitrac Mineral

Document version: May 20, 2024



Description

This mineral STOU (Super Tractor Oil Universal) multitrac SAE 15W-30 multifunctional agricultural oil has been specially developed for use in diesel engines, transmissions, power take-offs, wet brakes, hydraulic systems, power steering and end drive of among others tractors, combines, road and hydraulic engineering machines.

According to the specifications of

API CF-4 / CG-4 / GL-4
Allison C4
Ford M2C134-C / M2C134-D / M2C159-B / M2C159-C / M2C86-A
John Deere J27 / JD14B / JD20A / JD20C
MIL-L-2104D
MIL-L-2105
MIL-L-46152C
Massey Ferguson M-1135 / M-1139 / M-1143 / M-1144
New Holland 030C / 420A
ZF TE-ML 06B / 07B

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 36001 | 1 L | 6 | 450 |
| 36005 | 5 L | 4 | 112 |
| 36020 | 20 L | 1 | 30 |
| 36060 | 60 L | 1 | 6 |
| 36205 | 205 L | 1 | 2 |
| 36999 | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|--------|--------------------|
| Density at 15°C | 0.877 | kg/l |
| Viscosity | 15W-30 | |
| Kinematic Viscosity at 40°C | 81.7 | mm ² /s |
| Kinematic Viscosity at 100°C | 10.8 | mm ² /s |
| Viscosity Index | 118 | |
| Dynamic Viscosity at -20°C | 6600 | mPa.s |
| Flashpoint COC | 222 | °C |
| Pourpoint | -35 | °C |
| Total Base Number | 10.7 | mgKOH/g |

These characteristics are typical of current production. Variations in these characteristics may occur.